



DIN 966 Phillips Oval Countersunk Machine Screw								
Diameter	M2.5	M3	M3.5	M4	M5	M6	M8	M10
Length								
3	0.211							
4	0.242	0.350	0.536					
5	0.272	0.395	0.596	0.824				
6	0.302	0.439	0.656	0.902	1.49			
8	0.362	0.527	0.775	1.06	1.73	2.66		
10	0.422	0.615	0.894	1.21	1.98	3.01	6.14	
12	0.482	0.703	1.01	1.37	2.23	3.36	6.78	11.7
14	0.543	0.791	1.13	1.52	2.47	3.72	7.41	12.7
16	0.603	0.880	1.25	1.68	2.72	4.07	8.05	13.7
18	0.663	0.968	1.37	1.83	2.97	4.42	8.68	14.7
20	0.723	1.06	1.49	1.99	3.22	4.78	9.32	15.7
22	0.783	1.14	1.61	2.14	3.46	5.13	9.95	16.7
25	0.874	1.28	1.79	2.37	3.83	5.66	10.9	18.2
28		1.41	1.97	2.61	4.11	6.19	11.8	19.7
30		1.5	2.09	2.76	4.44	6.55	12.5	20.7
35			2.39	3.15	4.93	7.43	14.1	23.7
40				3.53	5.68	8.31	15.7	25.7
45					6.30	9.20	17.3	28.2
50					6.93	10.1	18.9	30.7
55							20.5	33.2
60								35.8



DIN 7985 Phillips Pan Head Machine Screw								
Diameter	M2.5	M3	M3.5	M4	M5	M6	M8	M10
Length								
3	0.34							
4	0.37	0.621						
5	0.40	0.666	0.99	1.40				
6	0.43	0.710	1.05	1.48	2.66			
8	0.49	0.798	1.17	1.63	2.91			
10	0.55	0.876	1.29	1.79	3.16	5.14	10.9	
12	0.61	0.954	1.42	1.94	3.41	5.49	11.5	21.2
14	0.67	1.03	1.54	2.10	3.66	5.84	12.2	22.2
16	0.73	1.11	1.67	2.25	3.91	5.29	12.8	23.2
18	0.79	1.19	1.80	2.41	4.16	5.64	13.5	24.2
20	0.85	1.27	1.92	2.56	4.41	6.00	14.2	25.2
22	0.91	1.35	2.05	2.72	4.66	6.35	14.8	26.2
25	1.00	1.47	2.25	2.94	5.03	6.87	15.8	27.7
28	1.09	1.59	2.50	3.24	5.4	7.40	16.8	29.2
30	1.18	1.71	2.63	3.44	5.7	7.75	17.5	30.2
35			3.4	3.94	6.5	8.60	19.1	32.7
40				4.44	7.3	9.50	20.7	35.2
45					8.0	10.4	22.3	37.7
50					8.7	11.3	23.9	41.2
55							25.4	43.7
60							27.0	46.2



Weight in kgs. per 1,000 pcs. unless otherwise specified. All weights are approximations.
All information is strictly informative